

PRODUKTINFORMATION



HÄMTFAX
08-580 941 14



FAX ON DEMAND
+46 8 580 941 14



INTERNET
<http://www.elfa.se>

TEKNISK INFORMATION 020-75 80 20 ORDERTEL 020-75 80 00 ORDERFAX 020-75 80 10

TECHNICAL INFORMATION +46 8 580 941 15 ORDERPHONE +46 8 580 941 01 ORDERFAX +46 8 580 941 11

— Vi reserverar oss mot fel samt förbehåller oss rätten till ändringar utan föregående meddelande —

ELFA artikelnr.

Antal sidor: 21

73-104-77 FR1216 Radio & TV tuner

DATA SHEET

FR1216

Desktop video & radio module system CCIR B/G

Preliminary specification
File under Display Components, DC03

1996 Jun 05

Desktop video & radio module system CCIR B/G

FR1216



FEATURES

- System CCIR B/G and FM radio broadcast
- True 5 V device (low power dissipation)
- Full TV frequency range from channel 2 (48.25 MHz) to channel 69 (855.25 MHz)
- FM band coverage from 87.5 to 108 MHz
- PLL controlled tuning
- True-synchronous vision IF demodulator (PLL)
- Demodulated video output, AF sound output, second sound IF output
- 10.70 MHz IF for external FM demodulation circuit
- I²C-bus control of tuning, address selection, AFC status information
- Complies with European regulations on radiation, signal handling and immunity ("CENELEC 55020, 55013" and "Amtsblatt 15/92")
- Small horizontally mounted metal housing.

DESCRIPTION

The FR1216 desktop TV/radio RF module is a combination of an FM radio, a TV VHF/UHF tuner and an IF demodulator in one small size metal case. It is designed to meet a wide range of RF applications in the PC Multi-Media environment.

The FR1216 has two 75 Ω inputs for both TV and audio FM broadcast reception. The input connectors are available in either standard Phono (female/female sockets) or IEC (female for TV/male for FM).

The tuning, bandswitching and input switching (both for TV and FM) are performed through the built-in digitally controlled I²C bus.

The PLL tuning system used enables tuning with step-size programmable between 31.25, 50.0 or 62.5 kHz. A DC-DC converter is built around the PLL synthesizer IC to provide the tuning voltage, thus making the FR1216 video & radio module a true 5 V device.

The FR1216 type offers a 10.70 MHz FM-IF output which can be connected to an external FM demodulation circuit. The automatic gain control (AGC) and analog-to-digital converter (ADC) functions are also made accessible via the pins in the FR1216 for external control of the overall gain and tuning in the FM mode.

The FR1216 meets the input immunity, signal handling and radiation requirements of CENELEC.

ORDERING INFORMATION

TYPE	DESCRIPTION	CATALOGUE NUMBERS
FR1216/HM/PH	standard phono	3139 147 13351
FR1216/HM/IEC	IEC	3139 147 13361

MARKING

The following items of information are printed on a sticker that is on the top cover of the tuner:

- Type number
- Code number
- Origin letter of factory
- Change code
- Year and week code.

INTERMEDIATE FREQUENCIES

SYSTEM	FREQUENCY ⁽¹⁾ (MHz)
	PAL B/G
Picture carrier	38.90
Colour	34.47
Sound 1	33.40
Sound 2	33.16
NICAM	33.05

Note

1. The oscillator frequency is above the input signal frequency.

CHANNEL COVERAGE

BAND	CHANNELS
FM band	87.50 to 108 MHz
Low band	48.25 to 170.00 MHz
Mid band	170.00 to 450.00 MHz
High band	450.00 to 855.25 MHz

Desktop video & radio module system CCIR B/G

FR1216


BLOCK DIAGRAM

Fig.1 Electrical block diagram.

**Desktop video & radio module
system CCIR B/G****FR1216****PINNING**

SYMBOL	PIN	DESCRIPTION
AGC	9	automatic gain control voltage
ADC	10	analog-to-digital converter input
V _T	11	tuning voltage (monitor)
V _{S(tuner)}	12	supply voltage tuner section +5 V
SCL	13	I ² C-bus serial clock
SDA	14	I ² C-bus serial data
AS	15	I ² C-bus address select
P3	20	system switch
FM-IF	21	10.70 MHz output
2 nd IF O/P	22	second IF sound output
CVBS	23	Composite Video Baseband Signal (CVBS) output
V _{S(IF)}	24	supply voltage IF section +5 V
AF O/P	25	AF sound output
–	TH1, TH2, TH3 and TH4	mounting tags (ground)

Desktop video & radio module system CCIR B/G

FR1216

LIMITING VALUES

Limiting values under operational conditions

The tuner can be guaranteed to function properly under the following conditions.

SYMBOL	PARAMETER	PIN	MIN.	TYP.	MAX.	UNIT
Z_{IAGC}	AGC input source impedance	9	—	—	500	Ω
Z_{IADC}	ADC input source impedance	10	—	—	500	Ω
$V_{S(tuner)}$	supply voltage	12	4.75	5.00	5.25	V
$V_{S(ripple)}$	peak-to-peak ripple voltage susceptibility (at 5 V $\pm 5\%$); note 1 20 Hz to 100 kHz >100 kHz to 500 kHz		—	—	20	mV
$I_{S(tuner)}$	supply current		—	—	120	mA
V_{SCL}	SCL bus input voltage	13	-0.3	—	+5.25	V
V_{SDA}	SDA bus input voltage	14	-0.3	—	+5.25	V
I_{SDA}	SDA bus current (open collector)		-1	—	+5	mA
V_{AS}	address select voltage; note 2	15	—	—	+5.25	V
Z_{IF}	2 nd IF sound output load impedance: DC AC	22	0.5	—	—	k Ω
Z_{CVBS}	Composite Video Baseband Signal load impedance: DC AC	23	—	75	—	Ω
t_L	CVBS load time constant		—	75	—	Ω
t_L	CVBS load time constant		—	—	100	ns
$V_{S(IF)}$	IF supply voltage	24	4.75	5.0	5.25	V
$V_{IF(ripple)}$	peak-to-peak ripple voltage susceptibility (at 5 V $\pm 5\%$); note 1 20 Hz to 100 kHz >100 kHz to 500 kHz		—	—	20	mV
$I_{S(IF)}$	IF supply current		—	—	100	mA
Z_{AF}	AF sound output load impedance: DC AC		—	—	—	k Ω
			25	1.0	—	k Ω
				0.6	—	k Ω

Notes

1. Sinusoidal ripple voltage superimposed on the 5 V supply voltage in the frequency range of 20 Hz to 500 kHz.
Criteria for TV interference >57 dB; criteria for FM interference >40 dB.
Conditions: FM deviation = 22.5 kHz; external filter 300 Hz to 20 kHz; 50 μ s de-emphasis.
2. For detailed information about the address decoding, refer to Chapter "Application information".

Desktop video & radio module system CCIR B/G

FR1216

Environmental conditions

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
Non-operational conditions						
T _{amb}	ambient temperature		-25	-	+85	°C
RH	relative humidity		-	-	100	%
g _B	bump acceleration	25 g	-	-	245	m/s ²
g _S	shock acceleration	50 g	-	-	490	m/s ²
	vibration amplitude	10 to 55 Hz	-	0.35	-	mm
Operational conditions						
T _{amb}	ambient temperature		-10	-	+60	°C
RH	relative humidity		-	-	95	%

OVERALL PERFORMANCE

Conditional data

SYMBOL	PARAMETER	VALUE	UNIT
T _{amb}	ambient temperature	25 ±5	°C
RH	relative humidity	60 ±15	%
V _{S(tuner)}	supply voltage (tuner section)	5 ±0.125	V
V _{S(IF)}	supply voltage (IF section)	5 ±0.125	V
Z _{CVBS}	video output load impedance (DC)	75	Ω
Z _{IF}	2 nd IF sound output load impedance	>500	Ω
t _{pr}	pre-heating time (+5 V at pin 24)	10	minute
Z _{S(AE)}	aerial source impedance (unbalanced)	75	Ω

Desktop video & radio module system CCIR B/G

FR1216

TUNER SECTION

Tuner characteristics

For detailed information about the PLL programming, refer to Chapter "Application information".


The desktop video tuner is guaranteed to function properly within the specified operational conditions, but a certain deterioration of performance parameters may occur at the limits of the operational conditions.

Required data for test equipment to be used

EQUIPMENT	PARAMETER	VALUE	UNIT
DC voltmeter	input impedance	>1	MΩ
Oscilloscope	input impedance: resistance capacitance	>1 <15	MΩ pF
Spectrum analyzer	input impedance	50	Ω
FET probe	input impedance: resistance capacitance	1 3.5	MΩ pF
	output impedance	50	Ω
	voltage gain	0	dB

Desktop video & radio module system CCIR B/G

FR1216

(1) BU4 loaded with $75\ \Omega$.(2) $50\ \mu\text{s}$ de-emphasis.

SA = Spectrum Analyzer.

P = FET probe.

DA = Distortion Analyzer.

VAC = dual channel AC voltmeter ($Z_i = 600\ \Omega$)

Fig.2 Typical test set up.

Desktop video & radio module system CCIR B/G

FR1216

Definitions of test signals (see Fig.2)

TEST SIGNAL	FREQ. (MHz)	AMPLITUDE	MODULATION	
			VIDEO	AUDIO
A0: unmodulated vision carrier	480.25	60 dB μ V		
A1: CCIR B/G standard signal with video modulation	480.25	60 dB μ V (top sync)	100% (rest carrier 10%) 2T pulse and bar	
B1: unmodulated sound carrier B/G system	485.75	-13 dB w.r.t. A0 to A1		
B2: FM modulated sound carrier B/G system	485.75	-13 dB w.r.t. A0 to A1		1 kHz; modulation frequency deviation ± 27 kHz; 50 μ s pre-emphasis
B3: unmodulated sound carrier B/G system	478.75	-13 dB w.r.t. A0 to A1		
C1: FM modulated sound carrier	87.5	60 dB μ V		1 kHz; modulation frequency deviation ± 75 kHz; 10% pilot carrier (L = R)
C2: FM modulated sound carrier	98.0	60 dB μ V		1 kHz; modulation frequency deviation ± 75 kHz; 10% pilot carrier (L = R)
C3: FM modulated sound carrier	108.0	60 dB μ V		1 kHz; modulation frequency deviation ± 75 kHz; 10% pilot carrier (L = R)
C4: FM modulated sound carrier	98.0	60 dB μ V		1 kHz; modulation frequency deviation ± 22.5 kHz
C5: unmodulated sound carrier	98.0	60 to 100 dB μ V		

Antenna input characteristics

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
VSWR	reflection coefficient TV mode FM mode	referred to 75 Ω impedance (TV mode: worst case on or between picture and sound carrier at maximum gain)	—	5	
V_{PSM}	surge protection voltage		5	—	kV
V_{ant}	antenna connection disturbance voltage	<1.75 GHz	—	46	dB μ V

**Desktop video & radio module
system CCIR B/G**

FR1216

General characteristics

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
f_b	frequency range: FM band low band mid band high band		87.50 48.25 175.25 455.25	— — — —	108.00 168.25 447.25 855.25	MHz MHz MHz MHz
Δf_b	margin: for FM band for low band for mid/high band		3 1.5 3	— — —	— — —	MHz MHz MHz
α_i	image rejection (nominal gain to 10 dB gain reduction): low band mid band mid band high band	<300 MHz >300 MHz	70 66 60 50	— — — —	— — — —	dB dB dB dB
α_{IF}	IF rejection (picture)		60	—	—	dB
Z_{IF}	$\frac{1}{2}$ IF susceptibility: E2 to E12 E21 to E69		75 60	— —	— —	$\text{dB}\mu\text{V}$ $\text{dB}\mu\text{V}$
α_s	sound-chrominance moiré rejection: off-air UHF	up to 40 dB gain control up to 30 dB minimum gain control	56 56	— —	— —	dB dB
m_x	cross modulation: in-channel in-band low band ($n \pm 2$) mid band ($n \pm 3$) high band ($n \pm 5$) out of band		70 78 78 84 —	— — — — 100	— — — — —	$\text{dB}\mu\text{V}$ $\text{dB}\mu\text{V}$ $\text{dB}\mu\text{V}$ $\text{dB}\mu\text{V}$ $\text{dB}\mu\text{V}$
	breakthrough susceptibility: E2 to E12; E21 to E69		60	—	—	$\text{dB}\mu\text{V}$

Desktop video & radio module system CCIR B/G

FR1216

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{osc}	oscillator voltage at all pins		–	–	70	$\text{dB}\mu\text{V}$
t_{li}	oscillators lock-in time	charge pump set logic HIGH	–	–	150	ms
α_{vs}	the video signal-to-sound interference ratio with the tuner exposed to sound signals in the audio frequency range 100 Hz to 10 kHz and sound pressure levels up to 105 dB (20 μPa)		40	–	–	dB
V_{ESD}	electrostatic discharge (ESD) on all pins	note 1	2	–	–	kV

FM radio characteristics

$G_{V(FM)}$	FM voltage gain	test signal C1	35	–	–	dB
$\alpha_i(FM)$	FM image rejection		57	–	–	dB
$\alpha_{IF(FM)}$	FM IF rejection		60	–	–	dB
$Z_{IF(FM)}$	1 st repeat spot interference		75	–	–	$\text{dB}\mu\text{V}$

Note

1. All the pins of the desktop video tuner are protected against electrostatic discharge (ESD) up to 2 kV. The product is classified in category B ("MIL-STD-883C").

Desktop video & radio module system CCIR B/G

FR1216

Video and audio characteristics (see Fig.2)

PARAMETER	TEST SIGNAL	TEST POINT	MIN.	TYP.	MAX.	UNIT
CVBS characteristics: video amplitude signal at pin 23 DC level sync pulse at pin 23	A1 (peak-to-peak value) A1	BU4 BU4	0.7 —	— 0.35	1.1 —	V V
Video amplitude drop with respect to modulation 0.1 MHz at $T_{amb} = 45^{\circ}\text{C}$: at 1 MHz at 2 MHz at 3 MHz at 4 MHz at 4.43 MHz	A1 A1 A1 A1 A1	BU4 BU4 BU4 BU4 BU4	-1.0 -1.5 -2.5 -4.0 -6.0	— — — — —	+1.0 +1.5 +1.5 +2.0 +2.0	dB dB dB dB dB
Sound carrier rejection	A1 (1 MHz) + B1	BU4	40	—	—	dB
Residual 40.4 MHz signal in video channel: level of 1.5 MHz	A1 + B3	BU4	—	—	68	dB μ V
Residual 77.8 MHz signal in video channel	A1	BU4	—	—	80	dB μ V
Second IF sound output level at level of 5.5 MHz	A1 + B1	BU5	84	—	—	dB μ V
Test on 2T pulse at $T_{amb} = 45^{\circ}\text{C}$: 2T pulse/bar response 2T pulse response	A1 A1	BU4 BU4	-2.5 —	— —	+2.5 +3.0	% %
CVBS S/N (unweighted)	A1 + B1	BU4	41	—	—	dB
Gain limited sensitivity at 1 dB reduction of video output	A1	BU4	—	—	30	dB μ V
Audio characteristics: AF output level measured via LP 20 kHz filter, RMS detector, 50 μ s de-emphasis THD (Total Harmonic Distortion) measured via LP 20 kHz filter, RMS detector, 50 μ s de-emphasis S/N measured via CCIR filter, peak CCIR detector, 50 μ s de-emphasis	A1 + B2 A1 + B2 A1 (6 kHz sine wave, black-to-white) + B1	BU6 BU6 BU6	0.25 — 41	0.35 — —	0.50 0.5 —	V % dB
AF 3 dB response measured via LP 20 kHz filter, RMS detector, de-emphasis off	A1 (black) + B1	BU6	16	—	—	kHz
AM suppression ratio	A1 + B2	BU6	40	—	—	dB

'Digital AFC status

PARAMETER	CONDITIONS	FREQUENCY (kHz)	DIGITAL READ-OUT
ADC word at I ² C-bus during read operation	input voltage at pin 10: 0.0 to 0.15V _{S(tuner)}	-125	00
	input voltage at pin 10: 0.15 to 0.30V _{S(tuner)}	-62.5	01
	input voltage at pin 10: 0.30 to 0.45V _{S(tuner)}	0	02
	input voltage at pin 10: 0.45 to 0.60V _{S(tuner)}	+62.5	03
	input voltage at pin 10: 0.60 to 1.00V _{S(tuner)}	+125	04

Desktop video & radio module system CCIR B/G

FR1216

APPLICATION INFORMATION

A detailed description of the I²C-bus specification, with applications, is given in brochure "The I²C-bus and how to use it". This brochure may be ordered using the code number 9398 393 40011.

WRITE mode

BYTE	BITS								
	7 MSB	6	5	4	3	2	1	0 LSB	A ⁽¹⁾
Address byte	1	1	0	0	0	MA1	MA0	0	A
Program divider byte 1	0	n14	n13	n12	n11	n10	n9	n8	A
Program divider byte 2	n7	n6	n5	n4	n3	n2	n1	n0	A
Control information byte 1	1	CP	T2	T1	T0	RSA	RSB	OS	A
Control information byte 2	P7	P6	P5	P4	P3	P2	P1	P0	A

Note

1. A = Acknowledge.

ADDRESS SELECTION

V_{S(tuner)} = +5 V (PLL supply voltage)

MA1	MA0	ADDRESS ⁽¹⁾	VOLTAGE AT PIN 15
0	0	#C0	0 to 0.1V _{S(tuner)}
0	1	#C2	0.2 to 0.3V _{S(tuner)}
1	0	#C4	0.4 to 0.6V _{S(tuner)}
1	1	#C6	0.9 to 1.0V _{S(tuner)}

Note

1. If the address select pin (AS, pin 15) is left floating, the internal bias will automatically set the address to #C2.

PROGRAMMABLE DIVIDER SETTINGS (BYTES 1 AND 2)

Divider ratio:

N = 16 × {f_{RF(pc)} + f_{IF(pc)}}, where (pc) is picture carrier and f_{RF} and f_{IF} are expressed in MHz

$$f_{osc} = \frac{N}{16} \text{ (MHz).}$$

$$N = (8192 \times n13) + (4096 \times n12) + (2048 \times n11) + (1024 \times n10) + (512 \times n9) + (256 \times n8) + (128 \times n7) + (64 \times n6) + (32 \times n5) + (16 \times n4) + (8 \times n3) + (4 \times n2) + (2 \times n1) + n0$$

Desktop video & radio module system CCIR B/G

FR1216

CONTROL BYTE

Charge pump settings:

CP = 1, for fast tuning

CP = 0, for moderate speed tuning with slightly better residual oscillator FM.

Test mode settings:

T2 = T1 = 0; T0 = 1, for normal operation.

PLL disabling:

OS = 0, for normal operation

OS = 1, for switching the charge pump to the high impedance state.

Ratio select bits

RSA	RSB	STEP SIZE
X	0	50 kHz
0	1	31.25 kHz (for slow picture search)
1	1	62.5 kHz (for normal picture search)

PORFS BYTE**Band switching**

BAND	BIT ⁽¹⁾							
	P0	P1	P2	P3 ⁽²⁾	P4	P5	P6	P7
Low band	0	0	0	X	0	1	0	1
Mid band	0	0	0	X	1	0	0	1
High band	0	0	0	X	1	1	0	0
FM band	0	0	1	X	0	1	0	1

Notes

1. X = don't care; P0 to P7 are output ports on the PLL device.
2. P3 is a system switch output for customer applications.

Desktop video & radio module system CCIR B/G

FR1216

TELEGRAM EXAMPLES (WRITE MODE)

Start - Adb - Ack - Db1 - Ack - Db2 - Ack - Cb - Ack - Pb - Ack - Stop.

Start - Adb - Ack - Cb - Ack - Pb - Ack - Db1 - Ack - Db2 - Ack - Stop.

Start - Adb - Ack - Db1 - Ack - Db2 - Ack - Cb - Ack - Stop.

Start - Adb - Ack - Db1 - Ack - Db2 - Ack - Stop.

Where:

Start = start condition

Adb = address byte

Ack = acknowledge

Db1 = divider byte 1

Db2 = divider byte 2

Cb = control byte

Pb = ports byte

Stop = stop condition.

Remark: for channel selection involving band switching, and to ensure smooth tuning to the desired channel without causing unnecessary charge pump action, it is recommended to consider the difference between wanted channel frequency (f_w) and the current channel frequency (f_c):

- If $f_w > f_c$, use telegram as:

Start - Adb - Ack - Db1 - Ack - Db2 - Ack - Cb - Ack - Pb - Ack - Stop

- If $f_w < f_c$, use telegram as:

Start - Adb - Ack - Cb - Ack - Pb - Ack - Db1 - Ack - Db2 - Ack - Stop.

Unnecessary charge pump action will result in very low tuning voltage ($V_T \approx 0$ V) which may drive the oscillator to extreme conditions.

Desktop video & radio module system CCIR B/G

FR1216

READ mode

The in-lock can be read by setting the R/W bit to 1.

BYTE	BITS								
	7 MSB	6	5	4	3	2	1	0 LSB	A ⁽⁵⁾
Address byte	1	1	0	0	0	MA1	MA0	1	A
Status byte	POR ⁽¹⁾	FL ⁽²⁾	I2 ⁽³⁾	I1 ⁽³⁾	I0 ⁽³⁾	A2 ⁽⁴⁾	A1 ⁽⁴⁾	A0 ⁽⁴⁾	A

Notes

1. POR = Power On Reset. POR is internally set to 1 in case $V_{S(tuner)}$ drops below 3 V. The POR bit is reset when an end of data is detected by the PLL IC.
2. FL = In-lock flag; FL = 1: loop is phase-locked. The loop must be phase-locked during at least 8 periods of the internal 7.8125 kHz reference frequency before the FL flag is internally set to 1.
3. I2, I1 and I0 = digital information for I/O ports P2, P1 and P0 respectively.
4. A2, A1 and A0 = built-in 5-level A/D converter on I/O port P6. AFC information to the controller of the IF section is available on pin 10 (see Table "Digital AFC status").
5. A = Acknowledge.

TELEGRAM EXAMPLES (READ MODE)

Start - Adb - Ack - STB - Ack - STB - - Stop (no Ack from processor = End-of-data).

Start - Adb - Ack - STB - - Stop (no Ack from processor = End-of-data).

Where:

STB = Status byte.

Video buffer

A video buffer is built into the video & radio module, to enable the unit to drive a 75Ω load directly. In case it is required to use the FR1216 as a replacement for the FI1216 in the same videocard, it is necessary to replace the 75Ω series resistor in the video card by a 0Ω series resistor. At the same time the $22 \text{ k}\Omega$ series resistor in the tuning supply must be removed.

I²C-bus load

The FR1216 contains a series resistor ($R = 100 \Omega$) in the SCL and SDA lines. Both lines also have a capacitive load of typical 56 pF (see Fig.3).




Fig.3 I²C-bus load.

Desktop video & radio module system CCIR B/G

FR1216

MECHANICAL DATA




Fig.4 Mechanical outline.

Desktop video & radio module system CCIR B/G

FR1216

Aerial connections

Standard-phono socket female $75\ \Omega$ and IEC female (TV) and male (radio).

Solderability

The solderability of pins and mounting tags when tested initially and after 16 hours steam ageing in accordance with "IEC 68-2-20", test Ta, method 1 (solder bath $235\ ^\circ\text{C}$ for 2 s), results in a wetted area of 95%. No de-wetting will occur when soldered at $260\ ^\circ\text{C}$ for 5 s.

Resistance to soldering heat

The product will not be damaged when tested in accordance with "IEC 68-2-20", test Tb, method 1A (solder bath $260\ ^\circ\text{C}$ for 10 ± 1 s).

Mass

Approximately 50 g.

Robustness of pins


The pins will not be damaged when tested in accordance with "IEC 68-2-21":

- Test Ua1, tensile of 10 N in axial direction
- Test Ua2, thrust of 4 N in axial direction.

Punching pattern of chassis PCB

Field rejects are often related to broken tag joints.

Therefore, the following punching pattern is recommended (see Fig.5).



Dimensions in mm.

Fig.5 Punching pattern seen from solder side.

Desktop video & radio module system CCIR B/G

FR1216

DEFINITIONS

Data sheet status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.

PURCHASE OF PHILIPS I²C COMPONENTS



Purchase of Philips I²C components conveys a license under the Philips' I²C patent to use the components in the I²C system provided the system conforms to the I²C specification defined by Philips. This specification can be ordered using the code 9398 393 40011.

Philips Components – a worldwide company

Argentina: IEROD, Av. Juramento, 1991-14.B, (1428) BUENOS AIRES, Tel. (541) 786 7635, Fax. (541) 786 9367.

Australia: PHILIPS COMPONENTS PTY Ltd, 34 Waterloo Road, NORTH RYDE NSW 2113, Tel. (02) 805 4455, Fax. (02) 805 4466.

Austria: PHILIPS COMPONENTS, Vertriebsgesellschaft m.b.H., Triester Strasse 64, A-1101 WIEN, P.O. Box 213, Tel. (01) 601 01 12 12, Fax. (01) 60 101 12 10.

Belgium: PHILIPS NEDERLAND B.V., Philips Components & Semiconductors, Postbus 90050, 5600 PB EINDHOVEN, Netherlands, Tel. (31) 40 2783 749, Fax. (31) 40 2788 399.

Belarus: PHILIPS OFFICE BELARUS, Hotel Minsk, Volodarski Str. 6, 220050 MINSK, Tel. (5172) 200 915, Fax. (5172) 200 773.

Brazil: PHILIPS COMPONENTS, Rua do Rocio 220 - 5th floor, 04552-903 - SÃO PAULO - SP, Tel. (011) 821 2333, Fax. (011) 829 1849.

Canada: PHILIPS ELECTRONICS Ltd., Philips Components, 601 Milner Ave., SCARBOROUGH, Ontario, M1B 1M8, Tel. (0416) 292 5161, Fax. (0416) 754 6248.

Chile: PHILIPS CHILENA S.A., Av. Santa Maria 0760, SANTIAGO, Tel. (02) 77 38 16, Fax. (02) 735 39 94.

China: PHILIPS COMPANY, Philips Components MSO PRC, 6/F Building 2 No. 889, Yi Shan Road, SHANGHAI 200233, Tel. (21) 485 0600, Fax. (21) 485 1015.

Colombia: IPRELENZO LTDA, Diagonal 59, No. 20-27, P.O. Box 77621, SANTA FE DE BOGOTA, Tel. (57) (1) 345 8713, Fax. (57) (1) 345 8712.

Denmark: PHILIPS COMPONENTS A/S, Prags Boulevard 80, P.O. Box 1919, 2300 COPENHAGEN S, Tel. (32) 883 333, Fax. (31) 571 949.

Finland: PHILIPS COMPONENTS, Sinikalliontie 3, FIN-02630 ESPOO, Tel. (9) 0-615 800, Fax. (9) 0-615 80920.

France: PHILIPS COMPOSANTS, 4 Rue du Port-aux-Vins, BP317, 92156 SURESNES, Cedex, Tel. (01) 4099 6161, Fax. (01) 4099 6427.

Germany: PHILIPS COMPONENTS UB der Philips G.m.b.H., P.O. Box 10 63 23, 20043 HAMBURG, Tel. (040) 2489 1330, Fax. (040) 2489 1426.

Greece: PHILIPS HELLENIQUE S.A., Components Division, No. 15, 25th March Street, GR 17778 TAVROS, Tel. (01) 4894 339/(01) 4894 911, Fax. (01) 4815 180.

Hong Kong: PHILIPS HONG KONG, Components Division, Unit 003-005, G/F, Hong Kong Ind. Technology Centre, 72 Tat Chee Avenue, Kowloon Tong, KOWLOON, Tel. (852) 2784 3000, Fax. (852) 2784 3003.

India: Philips INDIA Ltd., Components Dept., Shivsagar Estate, A Block, Dr. Annie Besant Rd. Worli, BOMBAY 400 018, Tel. (022) 4938 541, Fax. (022) 4938 722.

Indonesia: P.T. PHILIPS DEVELOPMENT CORPORATION, Philips House, Jalan H.R. Rasuna Said Kav. 3-4, P.O. Box 4252, JAKARTA 12950, Tel. (021) 520 1122, Fax. (021) 520 5189.

Ireland: PHILIPS ELECTRONICS (IRELAND) Ltd., Components Division, Newstead, Clonskeagh, DUBLIN 14, Tel. (01) 76 40 203, Fax. (01) 76 40 210.

Israel: Rapac Electronics Ltd., 7 Kehilat Saloniki St. P.O. Box 18053, TEL AVIV 61180, Tel. (03) 6450 444, Fax. (03) 6491 007.

Italy: PHILIPS COMPONENTS S.r.l., Piazza IV Novembre 3, 20124 MILANO, Tel. (02) 6752 2531, Fax. (02) 6752 2557.

Japan: PHILIPS JAPAN Ltd., Components Division, Philips Bldg 13-37, Kohnan 2-chome, Minato-ku, TOKYO 108, Tel. (03) 3740 5028, Fax. (03) 3740 0580.

Korea (Republic of): PHILIPS ELECTRONICS (KOREA) Ltd., Components Division, Philips House, 260-199 Itaewon-dong, Yongsan-ku, SEOUL, Tel. (02) 709-1472, Fax. (02) 709 1479.

Malaysia: PHILIPS MALAYSIA SDN BERHAD, Components Division, No. 76 Jalan Universiti, 46200 Petaling Jaya, KUALA LUMPUR, Tel. (03) 757 5511, Fax. (03) 757 4880.

PHILIPS MALAYSIA SDN BERHAD, Components Division, 345 Jalan Gelugor, PULAU PINANG, Tel. (04) 870 055, Fax. (04) 879 215.

Mexico: PHILIPS COMPONENTS, 5900 Gateway East, Suite 200, EL PASO, TX 79905, U.S.A., Tel. (915) 772 4020, Fax. (915) 772 4332.

Netherlands: PHILIPS NEDERLAND B.V., Philips Components & Semiconductors, Bldg. VB Postbus 90050, 5600 PB EINDHOVEN, Tel. (040) 2783 749, Fax. (040) 2788 399.

New Zealand: PHILIPS NEW ZEALAND Ltd., Components Division, 2 Wagener Place, C.P.O. Box 1041, AUCKLAND, Tel. (09) 849 4160, Fax. (09) 849 7811.

Norway: NORSK A/S PHILIPS, Philips Components, Box 1, Manglerud 0612, OSLO, Tel. (22) 74 8000, Fax. (22) 74 8341.

Pakistan: Philips Electrical Industries of Pakistan Ltd., Exchange Bldg. ST-2/A, Block 9, KDA Scheme 5, Clifton, KARACHI 75600, Tel. (021) 587 4641-49, Fax. (021) 577 035/587 4546.

Philippines: PHILIPS SEMICONDUCTORS PHILIPPINES Inc., 106 Valero St. Salcedo Village, P.O. Box 2108 MCC, MAKATI, Metro MANILA, Tel. (02) 810 0161, Fax. (02) 817 3474.

Poland: PHILIPS POLAND Sp. z.o.o. Components Division, ul. Lutkiska 10, 04-123 WARSZAWA, Tel. (22) 612 2594, Fax. (22) 612 2327.

Portugal: PHILIPS PORTUGUESA, S.A., Rua dr. António Loureiro Borges 5, Arquiparque - Miraflores, Apartado 300, 2795 LINDA-A-VELHA, Tel. (01) 416 3160/416 3333, Fax. (01) 416 3174/416 3366.

Russia: PHILIPS RUSSIA, ul. Usatccheva 35A, 119048 MOSCOW, Tel. (095) 247 9124, Fax. (095) 247 9132.

Singapore: PHILIPS SINGAPORE, Pte Ltd., Components Division, Lorong 1, Toa Payoh, SINGAPORE 1231, Tel. (65) 350 2000, Fax. (65) 355 1758.

South Africa: S.A. PHILIPS Pty Ltd., Components Division, 195-215 Main Road Martindale, 2092 JOHANNESBURG, P.O. Box 7430 Johannesburg 2000, Tel. (011) 470 5911, Fax. (011) 470 5494.

Spain: PHILIPS COMPONENTS, Balmes 22, 08007 BARCELONA, Tel. (93) 301 63 12, Fax. (93) 301 42 43.

Sweden: PHILIPS COMPONENTS AB, Kottbygatan 7, Akalla. Postal address: S-164 85 STOCKHOLM, Tel. (+46) 8 632 2000, Fax. (+46) 8 632 2745.

Switzerland: PHILIPS COMPONENTS AG, Allmendstrasse 140, CH-8027 ZÜRICH, Tel. (01) 488 22 11, Fax. (01) 481 77 30.

Taiwan: PHILIPS TAIWAN Ltd., 23-30F, 66, Chung Hsiao West Road, Sec. 1, Taipei, Taiwan ROC, P.O. Box 22978, TAIPEI 100, Tel. (02) 388 7666, Fax. (02) 382 4382.

Thailand: PHILIPS ELECTRONICS (THAILAND) Ltd., 209/2 Sanpavuth-Bangna Road Prakanong, Bangkok 10260, THAILAND, Tel. (66) 2 745 4090, Fax. (66) 2 398 0793.

Turkey: Türk Philips Ticaret A.S., Components Department, Talatpasa Cad. No. 5, 80640 GÜLTEPE/İSTANBUL, Tel. 90-212-279-27-70, Fax. 90-212-282-67-07.

Ukraine: PHILIPS UKRAINE Ltd., 2A Akademika Koroleva str., 252148 KIEV, Tel. (044) 476 0297, Fax. (044) 476 6991.

United Kingdom: PHILIPS COMPONENTS Ltd., The Mullard Building, Dorking Business Park, DORKING, Surrey, RH4 1HJ, Tel. (01306) 512 000, Fax: (01306) 512 345.

United States: PHILIPS COMPONENTS, Division Headquarters, 1440 Indianland road JUPITER, FL 33458, Tel. (561) 745 3300, Fax. (561) 745 3600.

For literature: (800) 447 3762.
PHILIPS DISPLAY COMPONENTS COMPANY,
1600 Huron Parkway, ANN ARBOR, Michigan 48105-2590,
Tel. (313) 996 9400, Fax. (313) 761 2776.

Uruguay: PHILIPS COMPONENTS, Coronel Mora 433, MONTEVIDEO, Tel. (02) 704 044, Fax. (02) 920 601.

For all other countries apply to: Philips Components, Marketing Communications, P.O. Box 218, 5600 MD EINDHOVEN, The Netherlands, Fax. +31-40-2724 547.

COD06 © Philips Electronics N.V. 1996

All rights are reserved. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner.

The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice. No liability will be accepted by the publisher for any consequence of its use. Publication thereof does not convey nor imply any license under patent- or other industrial or intellectual property rights.

Printed in The Netherlands



PHILIPS

Philips
Components

Let's make things better.