

SANYO	No.2020A	2SB1141/2SD1681
		PNP/NPN Epitaxial Planar Silicon Transistors 18V/1.2A Switching Applications

Applications

- Converters, relay drivers, low-voltage and high power AF Amp.

Features

- Low saturation voltage and excellent linearity of h_{FE} .
- Wide ASO.

() : 2SB1141

Absolute Maximum Ratings at Ta = 25°C

			unit
Collector-to-Base Voltage	V_{CBO}	(-)20	V
Collector-to-Emitter Voltage	V_{CEO}	(-)18	V
Emitter-to-Base Voltage	V_{EBO}	(-)5	V
Collector Current	I_C	(-)1.2	A
Collector Current (Pulse)	I_{CP}	(-)2.0	A
Collector Dissipation	P_C	1.5	W
		10	W
Junction Temperature	T_j	150	°C
Storage Temperature	T_{stg}	-55 to +125	°C

$T_c = 25^\circ\text{C}$

Electrical Characteristics at Ta = 25°C


			min	typ	max	unit
Collector Cutoff Current	I_{CBO}	$V_{CB} = (-)15\text{V}, I_E = 0$			(-)100	nA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = (-)4\text{V}, I_C = 0$			(-)100	nA
DC Current Gain	$h_{FE(1)}$	$V_{CE} = (-)2\text{V}, I_C = (-)100\text{mA}$	70*		400*	
	$h_{FE(2)}$	$V_{CE} = (-)2\text{V}, I_C = (-)1\text{A}$	40			
Gain-Bandwidth Product	f_T	$V_{CE} = (-)10\text{V}, I_C = (-)50\text{mA}$		150		MHz
Output Capacitance	C_{ob}	$V_{CB} = (-)10\text{V}, f = 1\text{MHz}$		(30)20		pF
C-E Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)500\text{mA}, I_B = (-)50\text{mA}$		(-)170	(-)400	mV
				120	300	mV
B-E Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)500\text{mA}, I_B = (-)50\text{mA}$		(-)0.85	(-)1.2	V
C-B Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10\mu\text{A}, I_E = 0$	(-)20			V
C-E Breakdown Voltage	$V_{(BR)CEO}$	$I_C = (-)1\text{mA}, R_{BE} = \infty$	(-)18			V
E-B Breakdown Voltage	$V_{(BR)EBO}$	$I_E = (-)10\mu\text{A}, I_C = 0$	(-)5			V

Continued on next page.

* : The 2SB1141/2SD1681 are classified by 100mA h_{FE} as follows

70	Q	140	100	R	200	140	S	280	200	T	400
----	---	-----	-----	---	-----	-----	---	-----	-----	---	-----

Package Dimensions 2042A
(unit : mm)




SANYO: TO126ML

2SB1141/2SD1681







Continued from preceding page.

		min	typ	max	unit
Turn-on Time	t_{on}		50		ns
Storage Time	t_{stg}		(60)200		ns
Fall Time	t_f		70		ns









Switching Time Test Circuit





Unit (Resistance : Ω , Capacitance : F)
 $I_C = 10I_{B1} = -10I_{B2} = 500\text{mA}$
 (For PNP, the polarity is reversed).



2SB1141/2SD1681



2SB1141/2SD1681



- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
 - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
 - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.