

**2SA1552/2SC4027****High-Voltage Switching Applications****Applications**

- Converters, inverters, color TV audio output.


**Features**

- Adoption of FBET, MBIT processes.
- High voltage and large current capacity.
- Fast switching time.
- Small and slim package permitting 2SA1522/2SC4027-applied sets to be made more compact.

**Package Dimensions**


unit:mm

2045B



unit:mm

2044B



() : 2SA1552

**Specifications****Absolute Maximum Ratings at Ta = 25°C**

Parameter	Symbol	Conditions	Ratings	Unit
Collector-to-Base Voltage	$V_{CB0}$		(-)180	V
Collector-to-Emitter Voltage	$V_{CEO}$		(-)160	V
Emitter-to-Base Voltage	$V_{EBO}$		(-)6	V
Collector Current	$I_C$		(-)1.5	A
Collector Current (Pulse)	$I_{CP}$		(-)2.5	A
Collector Dissipation	$P_C$		1	W
		$T_c=25^\circ\text{C}$	15	W
Junction Temperature	$T_J$		150	$^\circ\text{C}$
Storage Temperature	$T_{stg}$		-55 to +150	$^\circ\text{C}$

\* : The 2SA1552/2SC4027 are classified by 100mA  $h_{FE}$  as follows :

100 R	200	140 S	280	200 T	400
-------	-----	-------	-----	-------	-----

**SANYO Electric Co.,Ltd. Semiconductor Business Headquarters**


TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110-8534 JAPAN

# 2SA1552/2SC4027

## Electrical Characteristics at Ta = 25°C





Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Collector Cutoff Current	$I_{CB0}$	$V_{CB} = (-)120V, I_E = 0$			(-1.0)	$\mu A$
Emitter Cutoff Current	$I_{EB0}$	$V_{EB} = (-)4V, I_C = 0$			(-1.0)	$\mu A$
DC Current Gain	$h_{FE1}$	$V_{CE} = (-)5V, I_C = (-)100mA$	100		400	
	$h_{FE2}$	$V_{CE} = (-)5V, I_C = (-)10mA$	80			
Gain-Bandwidth Product	$f_T$	$V_{CE} = (-)10V, I_C = (-)50mA$		120		MHz
Output Capacitance	$C_{ob}$	$V_{CB} = (-)10V, f = 1MHz$		12		pF
				(22)		pF
Collector-to-Emitter Saturation Voltage	$V_{CE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		(-0.2)	(-0.5)	V
Base-to-Emitter Saturation Voltage	$V_{BE(sat)}$	$I_C = (-)500mA, I_B = (-)50mA$		0.13	0.45	V
Collector-to-Base Breakdown Voltage	$V_{(BR)CBO}$	$I_C = (-)10A, I_E = 0$	(-180)			V
Collector-to-Emitter Breakdown Voltage	$V_{(BR)CEO}$	$I_C = 1mA, R_{BE} = \infty$	(-160)			V
Emitter-to-Base Breakdown Voltage	$V_{(BR)EBO}$	$I_E = 10\mu A, I_C = 0$	(-6)			V
Turn-ON Time	$t_{on}$	See specified Test Circuit.		60		$\mu s$
Storage Time	$t_{stg}$	See specified Test Circuit.		(0.7)		$\mu s$
				1.2		
Fall Time	$t_f$	See specified Test Circuit.		(50)		$\mu s$
				80		

## Switching Time Test Circuit











$10I_{B1} = -10I_{B2} = I_C = 0.7A$   
For PNP, the polarity is reversed.





Unit (resistance :  $\Omega$ , capacitance : F)



# 2SA1552/2SC4027



## 2SA1552/2SC4027



■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1998. Specifications and information herein are subject to change without notice.