



**LF155-LF255-LF355
LF156-LF256-LF356
LF157-LF257-LF357**

**WIDE BANDWIDTH
SINGLE J-FET OPERATIONAL AMPLIFIERS**

- HIGH INPUT IMPEDANCE J-FET INPUT STAGE
- HIGH SPEED J-FET OP-AMPS : up to 20MHz, 50V/μs
- OFFSET VOLTAGE ADJUSTMENT DOES NOT DEGRADE DRIFT OR COMMON-MODE REJECTION AS IN MOST OF MONOLITHIC AMPLIFIERS
- INTERNAL COMPENSATION AND LARGE DIFFERENTIAL INPUT VOLTAGE CAPABILITY (UP TO V_{CC}^+)

TYPICAL APPLICATIONS


- PRECISION HIGH SPEED INTEGRATORS
- FAST D/A AND CONVERTERS
- HIGH IMPEDANCE BUFFERS
- WIDEBAND, LOW NOISE, LOW DRIFT AMPLIFIERS
- LOGARITHMIC AMPLIFIERS
- PHOTOCCELL AMPLIFIERS
- SAMPLE AND HOLD CIRCUITS

DESCRIPTION

These circuits are monolithic J-FET input operational amplifiers incorporating well matched, high voltage J-FET on the same chip with standard bipolar transistors.

This amplifiers feature low input bias and offset currents, low input offset voltage and input offset voltage drift, coupled with offset adjust which does not degrade drift or common-mode rejection.

The devices are also designed for high slew rate, wide bandwidth, extremely fast settling time, low voltage and current noise and a low 1/f noise level.




ORDER CODES


| Part Number | Temperature Range | Package | |
|---------------------|-------------------|---------|---|
| | | N | D |
| LF355, LF356, LF357 | 0°C, +70°C | • | • |
| LF255, LF256, LF257 | -40°C, +105°C | • | • |
| LF155, LF156, LF157 | -55°C, +125°C | • | • |

Example : LF355N


PIN CONNECTIONS (top view)



SCHEMATIC DIAGRAM



V_{io} ADJUSTMENT



ABSOLUTE MAXIMUM RATINGS

| Symbol | Parameter | Value | Unit | |
|-------------------|--------------------------------------|---|---------------------------------------|----|
| V _{CC} | Supply Voltage | ±22 | V | |
| V _i | Input Voltage - (note 1) | ±20 | V | |
| V _{id} | Differential Input Voltage | ±40 | V | |
| P _{tot} | Power Dissipation | 570 | mW | |
| | Output Short-circuit Duration | Infinite | | |
| T _{oper} | Operating Free Air Temperature Range | LF155-LF156-LF157 LF255-LF256-LF257 LF355-LF356-LF357 | -55 to +125 -40 to +105 0 to 70 | °C |
| T _{stg} | Storage Temperature Range | | -65 to 150 | °C |

ELECTRICAL CHARACTERISTICS

LF155, LF156, LF157 $-55^{\circ}\text{C} \leq T_{\text{amb}} \leq +125^{\circ}\text{C}$ $\pm 5\text{V} \leq V_{\text{CC}} \leq \pm 20\text{V}$
LF255, LF256, LF257 $-40^{\circ}\text{C} \leq T_{\text{amb}} \leq +105^{\circ}\text{C}$ $\pm 5\text{V} \leq V_{\text{CC}} \leq \pm 20\text{V}$
(unless otherwise specified)

| Symbol | Parameter | LF155 - LF156 - LF157 LF255 - LF256 - LF257 | | | Unit |
|----------------------|---|--|----------------------------------|----------------|--------------------------------------|
| | | Min. | Typ. | Max. | |
| V_{io} | Input Offset Voltage ($R_S = 50\Omega$) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 3 | 5 7 6.2 | mV |
| I_{io} | Input Offset Current - (note 3) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 3 | 20 20 1 | pA nA nA |
| I_{ib} | Input Bias Current - (note 3) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 20 | 100 50 5 | pA nA nA |
| A_{vd} | Large Signal Voltage Gain ($R_L = 2k\Omega$, $V_O = \pm 10\text{V}$, $V_{\text{CC}} = \pm 15\text{V}$) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | 50 25 | 200 | | V/mV |
| SVR | Supply Voltage Rejection Ratio - (note 4) | 85 | 100 | | dB |
| I_{CC} | Supply Current ($V_{\text{CC}} = \pm 15\text{V}$, no load) $T_{\text{amb}} = 25^{\circ}\text{C}$ | | 2 5 5 | 4 7 7 | mA |
| DV_{io} | Input Offset Voltage Drift ($R_S = 50\Omega$) | | 5 | | $\mu\text{V}/^{\circ}\text{C}$ |
| DV_{io}/V_{io} | Change in Average Temperature Coefficient with V_{io} adjust ($R_S = 50\Omega$) - (note 2) | | 0.5 | | $\mu\text{V}/^{\circ}\text{C}$ |
| V_{icm} | Input Common Mode Voltage Range ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$) | ± 11 | +15.1 -12 | | V |
| CMR | Common Mode Rejection Ratio | 85 | 100 | | dB |
| $\pm V_{\text{OPP}}$ | Output Voltage Swing ($V_{\text{CC}} = \pm 15\text{V}$) $R_L = 10k\Omega$ $R_L = 2k\Omega$ | ± 12 ± 10 | ± 13 ± 12 | | V |
| GBP | Gain Bandwidth Product ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$) LF155, LF255 LF156, LF256 LF157, LF257 | | 2.5 5 20 | | MHz |
| SR | Slew Rate ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$) $A_V = 1$ $A_V = 5$ | 7.5 30 | 5 12 50 | | V/ μs |
| R_i | Input Resistance ($T_{\text{amb}} = 25^{\circ}\text{C}$) | | 10^{12} | | Ω |
| C_i | Input Capacitance ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$) | | 3 | | pF |
| e_n | Equivalent Input Noise Voltage ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$, $R_S = 100\Omega$) $f = 1000\text{Hz}$ $f = 100\text{Hz}$ | | 20 12 12 25 15 15 | | $\frac{\text{nV}}{\sqrt{\text{Hz}}}$ |
| i_n | Equivalent Input Noise Current ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$, $f = 100\text{Hz}$ or $f = 1000\text{Hz}$) | | 0.01 | | $\frac{\text{pA}}{\sqrt{\text{Hz}}}$ |
| t_s | Settling Time ($V_{\text{CC}} = \pm 15\text{V}$, $T_{\text{amb}} = 25^{\circ}\text{C}$) - (note 5) LF155, LF255 LF156, LF256 LF157, LF257 | | 4 1.5 1.5 | | μs |

LF155 - LF156 - LF157

ELECTRICAL CHARACTERISTICS

LF355, LF356, LF357

$0^{\circ}\text{C} \leq T_{\text{amb}} \leq +70^{\circ}\text{C}$

$V_{\text{CC}} = \pm 15\text{V}$, (unless otherwise specified)

| Symbol | Parameter | LF355 - LF356 - LF357 | | | Unit |
|--------------------------------|---|---|----------------------|-----------------------|--|
| | | Min. | Typ. | Max. | |
| V_{io} | Input Offset Voltage ($R_{\text{S}} = 50\Omega$) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 3 | 10 13 | mV |
| I_{io} | Input Offset Current - (note 3) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 3 | 50 2 | pA nA |
| I_{ib} | Input Bias Current - (note 3) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | | 20 | 200 8 | pA nA |
| A_{vd} | Large Signal Voltage Gain ($R_{\text{L}} = 2\text{k}\Omega$, $V_{\text{O}} = \pm 10\text{V}$) $T_{\text{amb}} = 25^{\circ}\text{C}$ $T_{\text{min.}} \leq T_{\text{amb}} \leq T_{\text{max.}}$ | 25 15 | 200 | | V/mV |
| SVR | Supply Voltage Rejection Ratio - (note 4) | 80 | 100 | | dB |
| I_{CC} | Supply Current (no load) $T_{\text{amb}} = 25^{\circ}\text{C}$ | | | | mA |
| | | | | LF355 LF356, LF357 | |
| | | | 2 5 | 4 10 | |
| DV_{io} | Input Offset Voltage Drift ($R_{\text{S}} = 50\Omega$) - (note 2) | | 5 | | $\mu\text{V}/^{\circ}\text{C}$ |
| $DV_{\text{io}}/V_{\text{io}}$ | Change in Average Temperature Coefficient with V_{io} adjust ($R_{\text{S}} = 50\Omega$) | | 0.5 | | $\mu\text{V}/^{\circ}\text{C}$ per mV |
| V_{icm} | Input Common Mode Voltage Range ($T_{\text{amb}} = 25^{\circ}\text{C}$) | ± 10 | +15.1 -12 | | V |
| CMR | Common Mode Rejection Ratio | 80 | 100 | | dB |
| $\pm V_{\text{OPP}}$ | Output Voltage Swing | | | | V |
| | | $R_{\text{L}} = 10\text{k}\Omega$ $R_{\text{L}} = 2\text{k}\Omega$ | ± 12 ± 10 | ± 13 ± 12 | |
| GBP | Gain Bandwidth Product ($T_{\text{amb}} = 25^{\circ}\text{C}$) | | | | MHz |
| | | LF355 LF356 LF357 | 2.5 5 20 | | |
| SR | Slew Rate ($T_{\text{amb}} = 25^{\circ}\text{C}$) $A_{\text{V}} = 1$ $A_{\text{V}} = 5$ | | | | V/ μs |
| | | LF355 LF356 LF357 | 5 12 50 | | |
| R_{i} | Input Resistance ($T_{\text{amb}} = 25^{\circ}\text{C}$) | | 10^{12} | | Ω |
| C_{i} | Input Capacitance ($T_{\text{amb}} = 25^{\circ}\text{C}$) | | 3 | | pF |
| e_{n} | Equivalent Input Noise Voltage ($T_{\text{amb}} = 25^{\circ}\text{C}$, $R_{\text{S}} = 100\Omega$) $f = 1000\text{Hz}$ $f = 100\text{Hz}$ | | | | $\frac{\text{nV}}{\sqrt{\text{Hz}}}$ |
| | | LF355 LF356, LF357 LF355 LF356, LF357 | 20 12 25 15 | | |
| i_{n} | Equivalent Input Noise Current ($T_{\text{amb}} = 25^{\circ}\text{C}$, $f = 100\text{Hz}$ or $f = 1000\text{Hz}$) | | 0.01 | | $\frac{\text{pA}}{\sqrt{\text{Hz}}}$ |
| t_{s} | Settling Time ($T_{\text{amb}} = 25^{\circ}\text{C}$) - (note 5) | | | | μs |
| | | LF355 LF356, LF357 | 4 1.5 | | |

- Notes:**
1. Unless otherwise specified the absolute maximum negative input voltage is equal to the negative power supply voltage.
 2. The temperature coefficient of the adjusted input offset voltage changes only a small amount ($0.5\mu\text{V}/^{\circ}\text{C}$ typically) for each mV of adjustment from its original unadjusted value. Common-mode rejection and open loop voltage gain are also unaffected by offset adjustment.
 3. The input bias currents are junction leakage currents which approximately double for every 10°C increase in the junction temperature T_{amb} . Due to limited production test time, the input bias current measured is correlated to junction temperature. In a normal operation the junction temperature rises above the ambient temperature as a result of internal power dissipation, P_{tot} or $T_{\text{amb}} = T_{\text{amb}} + R_{\text{th(j-a)}} \times P_{\text{tot}}$ where $R_{\text{th(j-a)}}$ is the thermal resistance from junction to ambient. Use of a heatsink is recommended if input currents are to be kept to a minimum.
 4. Supply voltage rejection is measured for both supply magnitudes increasing or decreasing simultaneously, in accordance with common practise.
 5. Settling time is defined here, for a unity gain inverter connection using $2\text{k}\Omega$ resistors for the LF155, LF156 series. It is the time required for the error voltage (the voltage at the inverting input pin on the amplifier) to settle to within 0.01% of its final value from the time a 10V step input is applied to the inverter. For the LF157 series $A_{\text{V}} = -5$, the feedback resistor from output to input is $2\text{k}\Omega$ and the output step is 10V.

APPLICATION HINTS

The LF155, LF156, LF157 series are op amps with J-FET input transistors. These JFETs have large reverse breakdown voltages from gate to source or drain eliminating the need of clamps across the inputs. Therefore large differential input voltages can easily be accommodated without a large increase of input currents. The maximum differential input voltage is independent of the supply voltage. However, neither of the negative input voltages should be allowed to exceed the negative supply as this will cause large currents to flow which can result in a destroyed unit. Exceeding the negative common-mode limit on either input will cause a reversal of the phase to the output and force the amplifier output to the corresponding high or low state. Exceeding the negative common-mode limit on both inputs will force the amplifier output to a high state. In neither case does a latch occur since raising the input back within the common-mode range again puts the input stage and thus the amplifier in a normal operating mode. Exceeding the positive common-mode limit on a single input will not change the phase of the output however, if both inputs exceed the limit, the output of the amplifier will be forced to a high state. These amplifiers will operate with the common-mode input voltage equal to the positive supply. In fact, the common-mode voltage can exceed the positive supply by approximately 100 mV independent of supply voltage and over the full operating temperature range. The positive supply can therefore be used as a reference on an input as, for example, in a supply current monitor and/or limiter. Precautions should be taken to ensure that the power supply for the integrated circuit never becomes reversed in polarity or that the unit is not inadvertently installed backwards

in a socket as an unlimited current surge through the resulting forward diode within the IC could cause fusing of the internal conductors and result in a destroyed unit. Because these amplifiers are JFET rather than MOSFET input op amps they do not require special handling.


All of the bias currents in these amplifiers are set by FET current sources. The drain currents for the amplifiers are therefore essentially independent of supply voltages.

As with most amplifiers, care should be taken with lead dress, components placement and supply decoupling in order to ensure stability. For example, resistors from the output to an input should be placed with the body close to the input to minimize "pickup" and maximize the frequency of the feedback pole by minimizing the capacitance from the input to ground.


A feedback pole is created when the feedback around any amplifier is resistive. The parallel resistance and capacitance from the input of the device (usually the inverting input) to ac ground set the frequency of the pole. In many instances the frequency of this pole is much greater than the expected 3 dB frequency of the closed loop gain and consequently there is negligible effect on stability margin. However, if the feedback pole is less than approximately six times the expected 3 dB frequency a lead capacitor should be placed from the output to the input of the op amp. The value of that added capacitor should be such that the RC time constant of this capacitor and the resistance it parallels is greater than or equal to the original feedback pole time constant.







TYPICAL CIRCUITS

LARGE POWER BW AMPLIFIER




SETTLING TIME TEST CIRCUIT







SMALL SIGNAL PULSE RESPONSE




SMALL SIGNAL PULSE RESPONSE




SMALL SIGNAL PULSE RESPONSE




SMALL SIGNAL PULSE RESPONSE















SMALL SIGNAL PULSE RESPONSE















SMALL SIGNAL PULSE RESPONSE












PACKAGE MECHANICAL DATA
8 PINS - PLASTIC DIP




PM-DIP8.EPS

| Dimensions | Millimeters | | | Inches | | |
|------------|-------------|------|-------|--------|-------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | 3.32 | | | 0.131 | |
| a1 | 0.51 | | | 0.020 | | |
| B | 1.15 | | 1.65 | 0.045 | | 0.065 |
| b | 0.356 | | 0.55 | 0.014 | | 0.022 |
| b1 | 0.204 | | 0.304 | 0.008 | | 0.012 |
| D | | | 10.92 | | | 0.430 |
| E | 7.95 | | 9.75 | 0.313 | | 0.384 |
| e | | 2.54 | | | 0.100 | |
| e3 | | 7.62 | | | 0.300 | |
| e4 | | 7.62 | | | 0.300 | |
| F | | | 6.6 | | | 0.260 |
| i | | | 5.08 | | | 0.200 |
| L | 3.18 | | 3.81 | 0.125 | | 0.150 |
| Z | | | 1.52 | | | 0.060 |

DIP8.TBL

PACKAGE MECHANICAL DATA
8 PINS - PLASTIC MICROPACKAGE (SO)



PM-S08.EPS

| Dimensions | Millimeters | | | Inches | | |
|------------|-------------|------|------|--------|-------|-------|
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | | | 1.75 | | | 0.069 |
| a1 | 0.1 | | 0.25 | 0.004 | | 0.010 |
| a2 | | | 1.65 | | | 0.065 |
| a3 | 0.65 | | 0.85 | 0.026 | | 0.033 |
| b | 0.35 | | 0.48 | 0.014 | | 0.019 |
| b1 | 0.19 | | 0.25 | 0.007 | | 0.010 |
| C | 0.25 | | 0.5 | 0.010 | | 0.020 |
| c1 | 45° (typ.) | | | | | |
| D | 4.8 | | 5.0 | 0.189 | | 0.197 |
| E | 5.8 | | 6.2 | 0.228 | | 0.244 |
| e | | 1.27 | | | 0.050 | |
| e3 | | 3.81 | | | 0.150 | |
| F | 3.8 | | 4.0 | 0.150 | | 0.157 |
| L | 0.4 | | 1.27 | 0.016 | | 0.050 |
| M | | | 0.6 | | | 0.024 |
| S | 8° (max.) | | | | | |

S08.TBL

Information furnished is believed to be accurate and reliable. However, STMicroelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of STMicroelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. STMicroelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of STMicroelectronics.

© The ST logo is a trademark of STMicroelectronics

© 1998 STMicroelectronics – Printed in Italy – All Rights Reserved
STMicroelectronics GROUP OF COMPANIES

Australia - Brazil - Canada - China - France - Germany - Italy - Japan - Korea - Malaysia - Malta - Mexico - Morocco
The Netherlands - Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.

ORDER CODE :

