



SPM0101

Monolithic Microwave IC

Ultrasmall Low-noise Amplifiers


Features

- 1.Reduced noise and increased sensitivity.
- 2.Even further miniaturization achieved by the adoption of a miniature molded package (2.9×1.6mm).
- 3.Inclusion of input and output matching circuits means that no external circuits are required.
- 4.Suitable for 1st stage of receiver amp.

Package Dimensions

unit:mm

1272



Specifications


Absolute Maximum Ratings at Ta = 25°C

Parameter	Symbol	Conditions	Ratings	Unit
Maximum Supply Voltage	$V_{DD \max}$		5	V
Gate Voltage	V_G		-2	V
Total Allowable Power Dissipation	P_T		0.25	W
Channel Temperature	T_{ch}		150	°C
Storage Temperature	T_{stg}		-55 to +150	°C



Electrical Characteristics at Ta = 25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Drain Current	I_D	$V_{DD}=3V, V_G=0$	20	35	50	mA
Noise Factor	NF	$V_{DD}=3V, I_D=20mA, f=1.9GHz$		1.1	1.4	dB
Linear Gain	GL	$V_{DD}=3V, I_D=20mA, f=1.9GHz$		12.5		dB
VSWR (input)		$V_{DD}=3V, I_D=20mA, f=1.9GHz$		2.1		-
VSWR (output)		$V_{DD}=3V, I_D=20mA, f=1.9GHz$		2.1		-

Equivalent Circuit



Frequency Characteristics



■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of July, 1998. Specifications and information herein are subject to change without notice.