

WaveSources

Reno, Nevada 775-322-0968

V-1170-010-5

Surface Mount Voltage Controlled Oscillator

1150 - 1190 MHZ

Electrical Specifications, Test Data @ 25°C Subject to change without notice

PARAMETER	TEST CONDITIONS	UNITS	MIN	TYP	MAX
FREQUENCY RANGE		MHZ	1150.0		1190.0
TUNING VOLTAGE ³		V	0.5		4.5
MOD SENSE ¹		MHZ/V	12		23
OUTPUT POWER ^{1,2}		dBm		3.0	
PUSHING	VCC 4.75 – 5.25	MHZ/V		<1.0	<3.0
PULLING	@12db RL, All Angles	MHZ		<3.0	<5.0
POWER FLATNESS ^{1,2}		dBm			+/-2
HARMONICS ^{ALL}		dBc		-15	-12
SPURIOUS		dBc			-70
PHASE NOISE	SSB @1KHZ	dBc/HZ		-73	-70
	SSB @10KHZ	dBc/HZ		-103	-100
	SSB @100KHZ	dBc/HZ		-123	-120
	SSB @1000KHZ	dBc/HZ		-143	-140
TEMP RANGE		°C	-30		70
TEMP DRIFT		KHZ/°C		150	300
VCC		V	+4.75	+5.0	+5.25
ICC		MA			15
TUNE CAPACITANCE		PF			50

1. All data specified are with a 50 Ohm load termination.
2. Power Flatness is specified @ MIN, MAX frequencies, and Temp Range.
3. Guaranteed to Operate at 0 and 10 volts.