

# WaveSources

Reno, Nevada 775-322-0968

---

V-1650-010-5

Surface Mount Voltage Controlled Oscillator

1600 - 1700 MHZ

---

Electrical Specifications, Test Data @ 25°C Subject to change without notice

PARAMETER	TEST CONDITIONS	UNITS	MIN	TYP	MAX
FREQUENCY RANGE		MHZ	1600.0		1700.0
TUNING VOLTAGE <sup>3</sup>		V	0.5		4.5
MOD SENSE <sup>1</sup>		MHZ/V	27		41
OUTPUT POWER <sup>1,2</sup>		dBm		1.5	
PUSHING	VCC 4.75 – 5.25	MHZ/V		<1.8	3
PULLING	@12db RL, All Angles	MHZ		<4.0	8.0
POWER FLATNESS <sup>1,2</sup>		dBm			+/-2
HARMONICS <sup>ALL</sup>		dBc		<-12	-10
SPURIOUS		dBc			-70
PHASE NOISE	SSB @1KHZ	dBc/HZ		-69	-64
	SSB @10KHZ	dBc/HZ		-99	-94
	SSB @100KHZ	dBc/HZ		-119	-114
	SSB @1000KHZ	dBc/HZ		-132	-130
TEMP RANGE		°C	-20		65
TEMP DRIFT		KHZ/°C			
VCC		V	+4.75	+5.0	+5.25
ICC		MA			20
TUNE CAPACITANCE		PF			50

1. All data specified are with a 50 Ohm load termination.
2. Power Flatness is specified @ MIN, MAX frequencies, and Temp Range.
3. Guaranteed to Operate at 0 and 10 volts.