


5W TRIPLE OUTPUT DC-DC CONVERTER

Type	V _i	V _o	I _o
GS5T24-5D15	17,5 to 30	+ 5 V	200 mA
		+ 15 V	125 mA
		- 15 V	- 125 mA



DESCRIPTION


The GS5T24-5D15 is a 5W DC-DC converter designed to provide three isolated outputs: 5V/200mA and a dual $\pm 15V/\pm 125mA$.

The module operates from a 24V input source and offers 2500Vdc isolation voltage. A high level TTL/CMOS compatible input will enable the unit; a low input will inhibit it.

ELECTRICAL CHARACTERISTICS (T_{amb.} = 25° C unless otherwise specified)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Unit
V _i	Input Voltage	V _{o1} = 5V I _{o1} = 0 to 200mA V _{o2} = 15V I _{o2} = 0 to 125mA V _{o3} = -15V I _{o3} = 0 to -125mA	17.5	24.0	30.0	V
I _{ir}	Input Reflected Current	V _i = 17.5 to 30V Full Load on All Outputs			75	mApp
V _{o1}	Output Voltage 1	V _i = 17.5 to 30V I _{o1} = 0 to 200mA	4.75	5.00	5.25	V
V _{o2}	Output Voltage 2	V _i = 17.5 to 30V I _{o2} = 0 to 125mA	14.25	15.00	15.75	V
V _{o3}	Output Voltage 3	V _i = 17.5 to 30V I _{o3} = 0 to -125mA	- 14.25	- 15.00	- 15.75	V
V _{or1}	Output Ripple Voltage 1	V _i = 24V Full Load on All Outputs			30	mVpp
V _{or2}	Output Ripple Voltage 2	V _i = 24V Full Load on All Outputs			90	mVpp
V _{or3}	Output Ripple Voltage 3	V _i = 24V Full Load on All Outputs			90	mVpp
I _{o1}	Output Current 1	V _i = 17.5 to 30V V _{o1} = 5V	0		200	mA
I _{o2}	Output Current 2	V _i = 17.5 to 30V I _{o3} = 0 to 125mA V _{o2} = 15V	0		125	mA
I _{o3}	Output Current 3	V _i = 17.5 to 30V I _{o2} = 0 to -125mA V _{o3} = -15V	0		125	mA
V _{is}	Isolation Voltage		2500			VDC
f _s	Switching Frequency			120		kHz
η	Efficiency	V _i = 24V Full Load on All Outputs	65	70		%
T _{op}	Operating Ambient Temperature Range	Still air	0		+40	°C
T _{op}	Operating Ambient Temperature Range	Forced ventilation, air speed = 100 LFM	0		+60	°C
T _{stg}	Storage Temperature Range		- 20		+85	°C

CONNECTION DIAGRAM AND MECHANICAL DATA



Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specification mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics – All Rights Reserved

SGS-THOMSON Microelectronics GROUP OF COMPANIES
 Australia - Brazil - China - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands -
 Singapore - Spain - Sweden - Switzerland - Taiwan - Thailand - United Kingdom - U.S.A.