

The LA7221 is an electronic switch that was designed for use in audio video applications. It provides a wide dynamic range. The LA7221 has on-chip video clamp circuits (clamp elimination function).

### Features

- Low-voltage (5V) operation.
- Three inputs selectable and muting function.
- Video clamp circuits on chip.
- Wide dynamic range (2.0Vp-p or greater).


### Maximum Ratings at $T_a = 25^\circ\text{C}$

			unit
Maximum Supply Voltage	$V_{CC \text{ max}}$	7.0	V
Allowable Power Dissipation	$P_d \text{ max}$	100	mW
Operating Temperature	$T_{op}$	-10 to +70	$^\circ\text{C}$
Storage Temperature	$T_{stg}$	-40 to +125	$^\circ\text{C}$

### Operatings Characteristics at $T_a = 25^\circ\text{C}$ , $V_{CC} = 5.0\text{V}$

		min	typ	max	unit
Operating Voltage	$V_{CC \text{ op}}$	4.5	5.0	6.2	V
Current Dissipation	$I_{CC}$	3.5	4.6	6.6	mA
Maximum Input Level	$V_{IN \text{ max}}$	2.0	2.2		Vp-p
Frequency Characteristic	$G_F$		0	$\pm 0.5$	dB
Total Harmonic Distortion	THD		0.03	0.1	%
Crosstalk	CT		-70	-60	dB
Crosstalk Appearing in Muting Circuit	$CT_m$		-60	-50	dB
Output DC Offset	$\Delta V_{OUT}$		5	15	mV
CTL Changeover Level	$V_{CTL}$	1.0	1.4	1.8	V
Differential Gain	DG		0.5	1.0	%
Differential Phase	DP		0.5	1.0	deg

### Block Diagram and Application Circuit



### Truth Table


CTL.1	H	L	-	L
CTL.2	L	H	-	L
MUTE CTL	L	L	H	L
OUT	IN 1	IN 2	DC	IN 3

\*: The output is indeterminate at other states than shown above.

### Package Dimensions

(unit : mm)

3017C









**SANYO Electric Co., Ltd. Semiconductor Business Headquarters**

TOKYO OFFICE Tokyo Bldg., 1-10, 1 Chome, Ueno, Taito-ku, TOKYO, 110 JAPAN

# LA7221

## LA7221 Input / Output Configuration

Unit ( resistance:Ω )

Pin	Name	I/O Impedance or I/O Configuration	DC Voltage	Remarks
1	IN1	∞	 2.4V	
2	CONTROL 1		 0V	ON at 2.0V or greater
3	IN2	∞	 2.4V	
4	CONTROL 2		 0V	ON at 2.0V or greater
5	GND		0V	
6	IN3	∞	 2.4V	
7	MUTE CONTROL		 0V	ON at 2.0V or greater
8	OUT	20Ω	Emitter follower	Collector current 1.6mA
9	Vcc		5.0V	

■ No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.

■ Anyone purchasing any products described or contained herein for an above-mentioned use shall:

- ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use;
- ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.

■ Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of **December, 1996**. Specifications and information herein are subject to change without notice.