

The LA7800 is a multifunctional IC containing various required for synchronization, deflection of color television sets. This IC has been developed under the design concept that the basic characteristics should be made more complete and the television sets with this IC incorporated should be streamlined by making the device compact (DIP-16) and by minimizing the number of parts required.

### Functions

- Synchronizing separation
- Vertical oscillation
- Vertical blanking
- Horizontal AFC
- Vertical drive
- Horizontal oscillation
- X-ray protection

### Features

- Multifunction and compact(DIP-16)
- Minimum number of parts required
- Horizontal, vertical oscillators are stable against variations in ambient temperature and supply voltage due to small warm-up drift.
- Small variation in horizontal oscillation frequency
- Good linearity and interlace because DC bias at vertical output stage is subjected to sampling control within retrace time.
- Vertical blanking pulse width can be set freely according to peripheral parts.

### Maximum Ratings at Ta = 25°C

Parameter	Symbol	Value	Unit
Maximum Supply Voltage	V <sub>12</sub>	14	V
Maximum Supply Current	I <sub>15</sub>	16	mA
Allowable Power Dissipation	P <sub>d max</sub>	450	mW
Operating Temperature	T <sub>opr</sub>	-20 to +85	°C
Storage Temperature	T <sub>stg</sub>	-55 to +125	°C

### Recommended Operating Condition at Ta = 25°C

Parameter	Symbol	Value	Unit
Recommended Supply Voltage	V <sub>12</sub>	12	V


### Operating Characteristics at Ta = 25°C, V<sub>12</sub> = 12V, I<sub>CC15</sub> = 13mA

Parameter	Symbol	min	typ	max	unit
V <sub>CC12</sub> Current Dissipation	I <sub>CC12</sub>	13.0		20.0	mA
V <sub>CC15</sub> Supply Voltage	V <sub>CC15</sub>	11.8		13.2	V
Vertical Frequency Pull-In Range		9.0		11.0	Hz
Vertical Free-Running Frequency	f <sub>v</sub>	f <sub>v center</sub> 55Hz	50	60	Hz
Supply Voltage Dependence of Vertical Frequency		V <sub>12</sub> = 12 ± 1V, 55Hz at 12V	-0.5	0.5	Hz
Temperature Characteristic of Vertical Frequency		Ta = -10 to +60°C	-0.028	0.028	Hz/°C





Continued on next page.

### Package Dimensions

(unit :mm)  
3006B







Note) The Temperature characteristic of oscillation frequency represents the one for IC itself without peripheral parts.

- No products described or contained herein are intended for use in surgical implants, life-support systems, aerospace equipment, nuclear power control systems, vehicles, disaster/crime-prevention equipment and the like, the failure of which may directly or indirectly cause injury, death or property loss.
- Anyone purchasing any products described or contained herein for an above-mentioned use shall:
  - ① Accept full responsibility and indemnify and defend SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors and all their officers and employees, jointly and severally, against any and all claims and litigation and all damages, cost and expenses associated with such use:
  - ② Not impose any responsibility for any fault or negligence which may be cited in any such claim or litigation on SANYO ELECTRIC CO., LTD., its affiliates, subsidiaries and distributors or any of their officers and employees jointly or severally.
- Information (including circuit diagrams and circuit parameters) herein is for example only; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.