


SMALL SIGNAL SCHOTTKY DIODE
DESCRIPTION

General purpose metal to silicon diode featuring very low turn-on voltage and fast switching.

This device has integrated protection against excessive voltage such as electrostatic discharges.


ABSOLUTE MAXIMUM RATINGS (limiting values)

Symbol	Parameter		Value	Unit
V_{RRM}	Repetitive Peak Reverse Voltage		80	V
I_F	Forward Continuous Current	$T_j = 70\text{ }^\circ\text{C}$	500	mA
I_{FRM}	Repetitive Peak Forward Current	$t_p = 1\text{ s}$ $\delta \leq 0.5$	3	A
I_{FSM}	Surge non Repetitive Forward Current	$t_p = 10\text{ ms}$	10	A
T_{stg} T_j	Storage and Junction Temperature Range		- 65 to + 150 - 65 to + 125	$^\circ\text{C}$ $^\circ\text{C}$
T_L	Maximum Temperature for Soldering during 15s		260	$^\circ\text{C}$

THERMAL RESISTANCE

Symbol	Test Conditions	Value	Unit
$R_{th(j-l)}$	Junction-leads	110	$^\circ\text{C/W}$

ELECTRICAL CHARACTERISTICS
STATIC CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
I_R^*	$T_j = 25\text{ }^\circ\text{C}$	$V_R = 80\text{ V}$			200	μA
V_F^*	$T_j = 25\text{ }^\circ\text{C}$	$I_F = 10\text{ mA}$			0.32	V
	$T_j = 25\text{ }^\circ\text{C}$	$I_F = 100\text{ mA}$			0.42	
	$T_j = 25\text{ }^\circ\text{C}$	$I_F = 1\text{ A}$			1	

DYNAMIC CHARACTERISTICS

Symbol	Test Conditions		Min.	Typ.	Max.	Unit
C	$T_j = 25\text{ }^\circ\text{C}$	$f = 1\text{ MHz}$	$V_R = 0\text{ V}$		120	pF
			$V_R = 5\text{ V}$		35	

* Pulse test: $t_p \leq 300\mu\text{s}$ $\delta < 2\%$.

Figure 1. Forward current versus forward voltage at low level (typical values).




Figure 2. Forward current versus forward voltage at high level (typical values).




Figure 3. Reverse current versus junction temperature.




Figure 4. Reverse current versus V_{RRM} in per cent.




Figure 5. Capacitance C versus reverse applied voltage V_R (typical values).




Figure 6. Surge non repetitive forward current for a rectangular pulse with $t \leq 10$ ms.







Figure 7. - Surge non repetitive forward current versus number of cycles.




PACKAGE MECHANICAL DATA

MELF Glass



FOOT PRINT DIMENSIONS (Millimeter)



REF.	DIMENSIONS			
	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.80	5.20	0.19	0.20
B	2.55	2.65	0.10	0.10
C	0.45	0.55	0.02	0.02

Marking: ring at cathode end.
Weight: 0.15g

Information furnished is believed to be accurate and reliable. However, SGS-THOMSON Microelectronics assumes no responsibility for the consequences of use of such information nor for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of SGS-THOMSON Microelectronics. Specifications mentioned in this publication are subject to change without notice. This publication supersedes and replaces all information previously supplied. SGS-THOMSON Microelectronics products are not authorized for use as critical components in life support devices or systems without express written approval of SGS-THOMSON Microelectronics.

© 1994 SGS-THOMSON Microelectronics - Printed in Italy - All rights reserved.

SGS-THOMSON Microelectronics GROUP OF COMPANIES

Australia - Brazil - France - Germany - Hong Kong - Italy - Japan - Korea - Malaysia - Malta - Morocco - The Netherlands
Singapore - Spain - Sweden - Switzerland - Taiwan - United Kingdom - U.S.A.